


C - 852

R - 303

C - 854 / 8

Medico / Doctor Centrifuges

These are low priced units meeting the majority of the small capacity centrifuging requirements of medical practitioners, pathological laboratories and hospitals for routine centrifuging tests.

The units are fitted with resiliently mounted motor for vibration free performance having built in 5 step speed regulator. Available with Swing out or Angle rotor.

Technical Data						
Model	C-852	C-854/4	C-854/6	C-854/8	R-303	R-304
Capacity (ml)	4 x15	4 x15	6 x15	8 x15	8 x15	
Type of Rotor	Swing Out				Angle	
No. of Tubes	4	4	6	8	8	
Max. Speed (RPM)	3500	3500	3500	3500	3800	
Max. RCF ('g')	1750	1850	1600	1600	1450	
W x D x H (mm)	295 x 295 x 250	310 x 310 x 295			210 x 210 x 250	
Supply: 220-240 Volts, 50 Hz Single Phase.						

Compact Laboratory Centrifuges

R - 4C Compact model for routine work in medical and industrial laboratories has digital speed indicator and 0-60 minute digital countdown timer.

Salient Features :

- Stepless speed regulator
- Safety Lid interlock to prevent cover opening during centrifugation
- Wide choice of Swing out / Angle rotors and reduction adaptors


R-4C

Technical Data		
Models		R-4C
Max. Speed	rpm	4400
Max. RCF	'g'	2350
Max. Capacity	ml	200
W x D x H	mm	330 x 370 x 295

Supply: 220-240 Volts, 50 Hz Single Phase.

Rotor Listing				Reduction Adaptors (With Glass Tubes)					
Models	Capacity	Max. Speed	Max. RCF	RE 50-15RR (OLD RA-501)	RA-502	RA-151	RE 15-3R (OLD RA-152)	RE 15-5R (OLD RA-153)	RE 15-8R (OLD RA-154)
		RPM	'g'	(1 x 15ml)	(1 x 30ml)	(1 x 15ml)	(1 x 3ml)	(1 x 5ml)	(1 x 8ml)
Swing out Rotors (with glass tubes)									
R-41	8 x 15ml	3500	1850	X	X	X	✓	✓	✓
R-42	4 x 50ml	3500	1850	✓	X	X	X	X	X
Angle Rotors (with polypropylene tubes)									
R-43	8 x 15ml	4400	2340	X	X	✓	✓	✓	✓
R-44	4 x 50ml	4200	2350	✓	✓	X	X	X	X

Specifications subject to change without notice