

Salient Features:

- LED Display of Speed
- Compact unit, small foot print
- Last memory recall
- Small wall mounted power adaptor
- IP-42 Protection level
- Supplied with PTFE Stirring Paddle



MS-1 Plus

Technical Data	
Model	MS-1 Plus
Max Stirring Volume (Water)	1 Litre
Motor Type	Brushless
Speed range (RPM)	200-2000
Working Plate dia (mm)	135
Stirring paddle (PTFE coated) (mm)	11 x 30
Shell Protection Level	IP-42
Dimension (WxDxH) (mm)	168x160x47

Supply: 220-240 Volts, 50 Hz Single Phase.

Multi Magnetic Stirrers



MS-6P

Multi Magnetic Stirrer is useful where uniform mixing of multiple samples is required under identical or controlled conditions

Salient Features:

- 6 positions, capacity 500ml each
- Individual setting of speed & time for each position
- LCD Display of speed & time
- Incremental speed in 10 rpm

Technical Data	
Model	MS-6P
Number of Stirring Points	6
Max capacity	6 x 500ml
Working Plate dia (mm)	6 x (110 x 110)
Motor	Brushless motor
Speed Range (RPM)	50 -1500
Timer Range	1min-19h59min
Stirring Paddle (PTFE coated)	8 x 30 mm
Dimension (WxDxH)	220 x 430 x 65mm

Supply: 220-240 Volts, 50 Hz Single Phase.

Specifications subject to change without notice

