



RDHO 50



RDHO 80 (GMP)

REMI Dry hot air oven — RDHO series are specially designed to achieve extreme dryness by evaporating all moisture contents from the biomass or other material. Microprocessor control helps in achieving precise high temperature with forced convection. Suitable for varied applications in laboratories and scientific research institutions

GMP Models are with Inner & Outer Stainless Steel, 304 grade

Salient Features :

- Microprocessor PID controller (with timing function)
- Polished stainless-steel chamber with rounded corners for easy & quick cleaning
- Uniform distribution of air temperature
- Forced-air convection
- Double layer glass door, larger viewing window

Technical Data				
Model	RDHO 50	RDHO 80	RDHO 130	RDHO 220
Internal dimension (W × D × H) mm (Standard)	420 x 395 x 350	450 x 400 x 450	550 x 450 x 550	600 x 500 x 750
External dimension (W × D × H) mm (Standard)	720 x 590 x 520	740 x 618 x 630	935 x 860 x 850	980 x 930 x 1050
Internal dimension (W × D × H) mm (GMP)	420 x 395 x 350	450 x 400 x 450	550 x 450 x 550	600 x 500 x 750
External dimension (W × D × H) mm (GMP)	798 x 807 x 642	828 x 812 x 742	935 x 860 x 850	980 x 930 x 1050
Chamber Volume (Litres)	50	80	130	220
Temperature range	RT+10°C-300°C			
Temperature accuracy	±1°C			
Display resolution	0.1°C			
Timing range	1-9999min			
Shelves (Nos)	2	2	3	4
Power consumption (Watts)	1500	1500	2000	2600
Supply: 220-240 Volts, 50 Hz Single Phase.				

Specifications subject to change without notice