



RHI 50



RHI 80(GMP)

REMI heating incubators - **RHI** series are suitable for achieving precise incubation temperature of different laboratory samples required for optimizing reaction sensitivity

GMP Models are with Inner & Outer Stainless Steel, 304 grade

Salient Features :

- Microprocessor controller
- Interior is made of polished stainless steel with rounded corners for easy & quick cleaning.
- The space between the shelves is adjustable.
- Full inner glass door for easy observation
- Self-check function easy to identify problems.
- Over temperature and temperature difference alarms

Technical Data				
Model	RHI 50	RHI 80	RHI 160	RHI 270
Internal dimension (W × D × H) mm (Standard)	415 x 360 x 355	500 x 400 x 400	500 x 500 x 650	600 x 600 x 750
External dimension (W × D × H) mm (Standard)	670 x 480 x 500	765 x 515 x 545	800 x 885 x 875	900 x 990 x 980
Internal dimension (W × D × H) mm (GMP)	415 x 360 x 355	500 x 400 x 400	500 x 500 x 650	600 x 600 x 750
External dimension (W × D × H) mm (GMP)	715 x 745 x 580	800 x 700 x 625	800 x 885 x 875	900 x 990 x 980
Chamber Volume (Litres)	50	80	160	270
Shelves (Nos)	2	2	3	4
Temperature range / Accuracy	RT+5°C-65°C / ± 1°C			
Display resolution	0.1°C			
Timing range	1 min to 9999 min			
Type of heating	Forced air convection			
Power consumption (Watts)	300	400	1500	1500
Supply: 220-240 Volts, 50 Hz Single Phase.				

Specifications subject to change without notice