


RS-18 Plus

RS-12R

For gentle mixing of fluids in test tubes & glass vessels in pathology, microbiology, chemistry, molecular biology & biotechnology.

Model **RS-12 Plus & RS-18 Plus** shakers are with universal platform suitable to

accommodate interchangeable clamps of assorted sizes. A variety of clamps are available.

Model **RS-12R** shakers are with built-in speed regulator. These shakers have platform with 3 adjustable rollers.

Technical Data				
Model		RS-12 R	RS-12 Plus	RS-18 Plus
Speed Range	rpm	80 to 180	50 to 400	50 to 250
Platform Size	inches	7 x 11	12 x 12	20 x 20
Flasks Capacity (max)		-	5 x 500 ml	4 x 2000 ml
Overall Dimensions	W x D x H (mm)	270 x 260 x 156	320 x 415 x 130	520 x 613 x 155
Speed Indicator		Digital	Digital	Digital
Digital Count down Timer	minutes	199	199	199
Motor	Type	PMDC	Brushless DC	
Shaking Orbit	mm	10	10	10

Supply: 220-240 Volts, 50 Hz Single Phase.

Essential Clamps for RS-12 Plus & RS-18 Plus								
Models	Platform Size	Max. Volume	Max. No. of clamps (To be ordered separately)					
			2000 ml.	1000 ml.	500 ml.	250 ml.	150 ml.	100ml/ 50ml
RS-12 Plus	12" x 12"	2.5 Litres	-	-	5	9	9	9
RS-18 Plus	20" x 20"	9 Litres	4	9	13	25	25	25


RS-10 Pro

Rocker Shakers

Salient Feature:

- Timing Function
- Adjustable speed
- Speed increases in step of 1 RPM
- Choice of timed & Continuous mode
- Suitable for a variety of containers

Technical Data	
Model	RS - 10 Pro
Motor	Geared
Speed	10 - 80rpm
Timer Range	1min - 24hrs
Max Load	2kg
Display	LCD
Tilt Angle	7°
Tray size in mm	Silicone tray 250 x 250
Dimensions (WxDxH)	355 x 260 x 135 mm

Supply: 220-240 Volts, 50 Hz Single Phase

Specifications subject to change without notice