


RWB-6
RWB-12

REMI Water Bath is multipurpose water bath with six holes/ twelve holes to hold different size samples for easy & hygienic heating. Water Bath provides precise and constant temperature helps achieving uniform heating for the samples.

Salient Features:

- Microprocessor control with timing function
- Digital display
- Audible and visual alarm for over temperature
- **GMP versions with Inner & Outer SS 304**

Technical Data

Parameter	RWB - 6	RWB - 12
Temperature Range	RT $\pm$ 5°C ~99°C	RT $\pm$ 5°C ~99°C
Temperature Stability	$\pm$ 0.5°C	$\pm$ 0.5°C
Deviation Ability	$\pm$ 2°C	$\pm$ 2°C
Chamber Volume	15 Ltrs	28 Ltrs
Interior Dimension (W x D x H) (mm)	450 x 300 x 110	500 x 390 x 125
Timing Range	1~999 min.	1~999 min.
No. of hole	Six holes	Twelve holes
Heater Capacity (Watts)	1500	3000
Supply: 220-240 Volts, 50 Hz Single Phase.		

Water Bath Shakers


RSB - 12
Water Bath Shaker RSB - 12

These Water bath Shakers have wide applications in Biotechnology, Micro - Biology, Chemistry, Quality Control and other life sciences laboratories. The bath has size of 355 mm (W) x 300 mm (D) x 165 mm (H). A special pyramid type cover provided avoids evaporation of water and makes condensed water to fall back in the bath. A cock is provided to facilitate draining of Bath contents

The removable stainless steel tray houses lotus clamps for variety of flask capacities. **Standard unit supplied with tray accommodating 12 flasks x 100 ml.**

Following capacity are available optionally.

50 ml x 12 flasks	150 ml x 9 flasks
250 ml x 6 flasks	500 ml x 4 flasks
1000 ml x 2 flasks	2000 ml x 1 flask
Test Tube racks	

Salient Features:

- Inner chamber and outer body of SS 304
- Heating up to 95°C
- Digital Temperature Indicator cum Controller with precise accuracy of $\pm$ 1°C
- Shaking speed range from 40 to 180 strokes per min
- Stroke length 25 mm

Supply: 220-240 Volts 50 Hz Single Phase

Specifications subject to change without notice