

NEW
INTRODUCTION

RCO-150 Plus

CO₂ Incubators find applications in tissue engineered products, in-vitro fertilization, diagnostics, cancer research and other medical, pharmaceutical related industries. CO₂ Incubator are used to culture cells to provide it with the optimum temperature, moisture (sterile environment) and to maintain optimum pH under a CO₂ atmosphere.

Salient Features:

- Imported infrared CO₂ Sensor.
- CO₂ concentration Restoration Speed.
- Polished stainless-steel chamber, rounded corners for easy cleaning. Adjustable shelves.
- HEPA Microorganism Filter at Inlet provides 99% filtration of bacteria and dust ($\Phi < 0.3\mu m$) and supplies pure CO₂ into the incubator.
- Door temperature controller prevents condensate water on glass door of incubator effectively.
- Independent audio-visual temperature limiting alarm system.
- Alarm function for temperature difference, CO₂ over concentration and concentration difference, door open time, UV working status.
- Automatic control of fan speed to maintain uniform temperature and prevent damage to samples.
- Hot air sterilizing circulation system.
- PID controller with large LCD screen ensures precise and reliable control

Technical Data		
Model	RCO-80 Plus	RCO-150 Plus
Chamber Volume (Litres)	80	150
Sensor	Infrared Co ₂	
Heating Method	Air-Jacketed, PID Control	
CO Range	0~20% V/V	
CO Control resolution	± 0.1% (IR sensor)	
Temperature Range / Accuracy	RT+5~55°C / ± 1°C	
Humidity Method	Natural vaporization > 95%	
CO Recovery	(Door opens 30s, recovery to 5%) = 3 min	
Temperature Recovery	(Door opens 30s, recovery to 37°C) = 8 min	
Shelves	2	3
Internal Dimension (mm) (W x D x H)	400 x 450 x 500	480 x 530 x 610
External Dimension (mm) (W x D x H)	590 x 687 x 790	670 x 767 x 880

Supply: 220-240 Volts, 50Hz Single Phase

Specifications subject to change without notice

